

VENETIAN BLINDS 25mm


FITTING GUIDE

What you will need




Child Safety

Young children can be strangled by loops in pull cords, chains, tapes and inner cords that operate the product. To avoid strangulation and entanglement keep cords out of the reach of young children. Cords may become wrapped around a child's neck. Move beds, cots and furniture away from window covering cords. Do not tie cords together. Make sure cords do not twist and create a loop.




Safety Devices

This product has been supplied with a breakaway safety tassel pre-fitted to the lift cords. If a horizontal force is applied to the cords entering the tassel, it will safely break apart thereby eliminating any hazardous loops. These components have been supplied to make this blind safe in line with the new child safety regulations outlined in BS EN13120.




If the safety tassel becomes separated, first untwist and untangle the cords. Place the cords into one half of the tassel and press the tassel together until it is fully closed. You can test it by placing your arm between the cords and pressing downwards. The tassel should break apart with minimal force.



Fitting The Cord Safety Cleat

The safety cleat needs to be installed as close as possible to the headrail and in all cases not less than 1500mm from the floor. The cords must be fully wrapped around the safety cleat(s) when the blind is not in use. Refer to the table to determine the distance required between the cleats to fully accumulate the cords when the blind is completely raised up.

Drop of Blind	*Distance between cord cleats (centre to centre)
1-1000mm	100mm
1001 - 2000mm	150mm
2001-3000mm	300mm



Place the safety cleat in the desired position on the wall and mark the positions of the holes with a pencil. With the hole positions marked, drill as required use the screws provided to attach the safety cleat to the wall.

WARNING



Children can strangle if this safety device is not installed. Always use this device to keep cords or chains out of reach of children. Wrap the cords around the cord cleats in a figure of 8. When the cords are fully accumulated, ensure they are secure so that when any cord is pulled, no excess cord is released.




Venetian Blind System 25mm

Preparation

1. Confirm the location of the brackets on the window, options are: Top fix or face fix as shown opposite.
2. Mark with a pencil where the brackets are to be fixed. The first two brackets should be placed as close to the ends of the blind as possible ensuring that the brackets avoid the control mechanism.




Larger blinds will require the remainder of the brackets supplied to be spaced evenly throughout the width of the head rail to ensure sufficient support. Ensure they do not obstruct any moving parts inside the headrail.



Fitting the Blind

1. Install brackets firmly into place, use raw plugs where necessary to ensure brackets are secure. When positioning the brackets inside the window recess, make sure to allow for any obstructions such as window handles etc.

STEP 1



Locate the front lip of the headrail into the front of the bracket.

STEP 2

Push the front of the headrail inwards and the back of the headrail in an upwards direction until it locks into the back of the bracket.

